olivetti Praxis 45D

Electronic Typewriter

Three pitches (10, 12, 15)
Interchangeable "daisy wheel" printing element and ribbon cartridge
Display for electronic correction
One-line memory for automatic correction of characters, words or sentences

FEATURES AND CHARACTERISTICS

Display
16 character capacity of which 12 characters are for keyboard data entry, 1 is a separation character and 3 are service characters.
By using the corresponding keys you may:
- move the current line being typed forward or backward
- cancel or substitute characters allowing for the creation of first time final copy.

Automatic correction on the current line of typing
The one-line memory enables characters, words or sentences on the current line in process to be automatically cancelled, simply by activating the related cancel key.

Automatic return

Title centering

Paragraph indentation

Alphabetic and decimal tabulation

Automatic vertical lines

Multilingual capability

Automatic relocation of typing point

Auxiliary devices
On/off switch.
Paper support.
Anti-glare shield.
Acoustic cover.

Keyboard
Alphanumeric and function keys.
44 alphanumeric keys (100 printable characters) and 17 function keys.
REPEAT key (for repetitive use of any key).
Two shift keys.
Shift lock.
Automatic repeating space bar.
Automatic repeating return and vertical spacing.
Return without vertical spacing.
Tabulator setting key.
Tabulator clearing key.
Alphabetic tabulation key.
Cancel key (automatic for the last ten characters typed).
Automatic repeating backspace key.
Left & right-hand margin setting keys.
Margin release key.
Forward half space key.
Automatic relocate typing point key.
Code key.
Center key.
Indent key.
Decimal tab key
Forward key.
Standard master line when the typewriter is switched on.

Three-position spacing selector
1/10" Pica spacing
1/12" Elite spacing
1/15" Mikron spacing

Four-position line selector
Situated near left platen knob.

Two-position keyboard selector
KB I – for using the national keyboard
KB II – for using the second keyboard fitted with supplementary characters for typing in various foreign languages.

Signals
Typewriter is operative (red light).
Activated upper case (yellow light).
Audible end-of-line signal.

Casing
Casing in ABS, with hinged cover.

Electrical specification
Power supply: 115V
Frequency: 60 Hz.

Print unit
Speed: average 12 cps.
Fixed carriage, to take paper up to 13" wide.
Length of printing line: 11".
The upper part of the machine houses the following devices:
- platen release knob
- end-of-page indicator
- sliding paper guide
- paper release lever
- bail rod.

The type impact control is located under the cover.
Above the keyboard there are three graduated scales for the three spacings indicating the printhead movement with respect to the platen.
Interchangeable ribbon cartridge.
Available in three versions: fabric, carbon and correctable carbon.
Correction tape.
Capacity: approx. 1,100 characters.
Available in two versions:
LIFT-OFF for use with correctable carbon ribbon
COVER-UP for use with fabric or carbon ribbon.
Printing element.
Single interchangeable "daisy wheel" printing element.
Available in a variety of typestyles according to the type of spacing being used.

Dimensions and weight

Width:	18.7 inches	(47.7 cm)
Height:	5.3 inches	(13.5 cm)
Depth:	15.0 inches	(38.0 cm)
Weight:	19.4 pounds	(8.8 kg)

Dimensions and weight of packing
(Parcel post dimensions)

Width:	22.4 inches	(57.0 cm)
Height:	9.3 inches	(23.5 cm)
Depth:	19.3 inches	(49.0 cm)
Weight:	23.1 pounds	(10.5 kg)

olivetti

Olivetti Corporation
155 White Plains Road
Tarrytown, New York 10591

79567 Printed in USA 6-82